

## Seat Belt for Forklift

Forklift Seat Belts - This guideline reason is to be able to explain the Regulation requirements for the utilization of driver seatbelts or restraints on lift trucks. It is the employers' liability to be able to ensure that every machinery, piece of equipment and tool in the workplace is chosen and used rightly and worked in accordance with the manufacturer's directions.

Rough Terrain lift trucks ought to meet the regulations of ANSI Standard ASME B56.6-1992 with regards to their use, design, maintenance, inspection and fabrication.

Side boom tractors and mobile machine together with a Rollover Protective Structure, or ROPS for short, have to have seat belts that satisfy the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whichever mobile equipment includes seat belts required by law, the operator and subsequent passengers must make certain they utilize the belts each time the motor vehicle is in motion or engaged in operation since this can cause the machinery to become unstable and hence, unsafe.

If a seat belt or other driver restraint is needed on a lift truck.

The seat belt requirements while working a lift truck depend on different factors. Whether or not the lift truck is outfitted together with a Rollover Protective Structure, the kind of lift truck itself and the year the forklift was made all add to this determination. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

With regards to to a driver restraint device, enclosure or system, ANSI Standard ASME B56.1-1993 in the case of powered industrial trucks, is designed to aid the operator in lessening the probability of entrapment of the torso and/or head between the truck and the ground in the event of a tip over. The system or restraint device might consist of a seat belt, although a seat belt is not necessarily a part of such device or system.